



LPG

STEEL PORTABLE



SPECIFICATIONS

| MODEL/SIZE (LBS.) | 4.25 | 11 | 20 | 30 | 40 | 43.5 | 60 | 100 |
|-------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| HEIGHT (IN.) | 11.8 | 16.8 | 17.8 | 23.7 | 29.3 | 32.5 | 44.1 | 48.7 |
| HEIGHT (MM) | 300 | 427 | 452 | 602 | 744 | 825.5 | 1,120 | 1,240 |
| LPG CAPACITY (GAL) | 1 | 2.6 | 4.7 | 7.1 | 9.4 | 10.3 | 14.2 | 23.6 |
| LPG CAPACITY (LITER) | 3.8 | 9.8 | 17.8 | 26.9 | 35.6 | 39 | 53.8 | 89.3 |
| WATER CAPACITY (LBS.) | 12 | 26.2 | 47.6 | 71.5 | 95.2 | 103.6 | 142.9 | 239 |
| WATER CAPACITY (KG) | 5.4 | 11.9 | 21.6 | 32.4 | 43.2 | 47 | 64.8 | 108.4 |
| NOMINAL TARE WEIGHT (LBS.) | 11 | 13.1 | 16.6 | 23.5 | 29.1 | 33.9 | 48.1 | 68 |
| NOMINAL TARE WEIGHT (KG) | 5 | 5.9 | 7.5 | 10.6 | 13.2 | 15.4 | 21.8 | 30.8 |
| CYLINDER DIAMETER (IN.) | 9.1 | 9.1 | 12.3 | 12.3 | 12.3 | 12.3 | 12 | 14.7 |
| CYLINDER DIAMETER (MM) | 231 | 231 | 312 | 312 | 312 | 312 | 305 | 373 |
| CYLINDER VOLUME (CU. IN.) | 332 | 725 | 1,318 | 1,980 | 2,635 | 2,868 | 3,955 | 6,616 |
| CYLINDER VOLUME (LITER) | 5.4 | 11.9 | 21.6 | 32.4 | 43.2 | 47 | 64.8 | 108.4 |
| COLLAR DIAMETER (IN.) | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 |
| COLLAR DIAMETER (MM) | 165 | 165 | 165 | 165 | 165 | 165 | 165 | 165 |
| COLLAR HEIGHT (IN.) | 4 | 4 | 4 | 4 | 4 | 5.1 | 5.1 | 5.1 |
| COLLAR HEIGHT (MM) | 102 | 102 | 102 | 102 | 102 | 130 | 130 | 130 |
| FOOTRING DIAMETER (IN.) | 9.1 | 7.8 | 7.8 | 7.8 | 7.8 | 12 | 12 | 14.5 |
| FOOTRING DIAMETER (MM) | 231 | 198 | 198 | 198 | 198 | 305 | 305 | 368 |
| HORIZONTAL | N/A | N/A | Available | Available | Available | N/A | N/A | N/A |
| STANDARD SPECIFICATION | DOT-4BA-240 | DOT-4BA-240 | DOT-4BA-240 | DOT-4BA-240 | DOT-4BA-240 | DOT-4BA-240 | DOT-4BW-260 | DOT-4BW-240 |

All dimensions are approximate.